

# RF Exposure Report

**Applicant:** Dragino Technology Co., Limited.

**Address of Applicant:** Room 202,BaoChengTai industrial park,No.8 CaiYun LongCheng Street,LongGang District, Shenzhen 518116, China

**Manufacturer/Factory:** Dragino Technology Co., Limited.

**Address of Manufacturer/Factory:** Room 202,BaoChengTai industrial park,No.8 CaiYun LongCheng Street,LongGang District, Shenzhen 518116, China

**Equipment Under Test (EUT)**

Product Name: LoRaWAN Gateway

Model No.: DLOS8

Trade Mark: Dragino

**Applicable standards:** EN IEC 62311: 2020

**Date of sample receipt:** Oct. 12, 2020

**Date of Test:** Oct. 12 – Nov. 03, 2020

**Date of report issue:** Nov. 04, 2020

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The protection requirements with respect to electromagnetic compatibility contained in Directive 2014/53/EU are considered.



**Robinson Lo**  
**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
<i>00</i>	<i>Nov. 04, 2020</i>	<i>Original</i>

**Prepared By:**

**Date:**

*Nov. 04, 2020*

\_\_\_\_\_  
**Project Engineer**

**Check By:**

**Date:**

*Nov. 04, 2020*

\_\_\_\_\_  
**Reviewer**

## 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 GENERAL INFORMATION .....	4
4.1 GENERAL DESCRIPTION OF EUT .....	4
4.2 TEST FACILITY .....	5
4.3 TEST LOCATION .....	5
4.4 DESCRIPTION OF SUPPORT UNITS .....	5
4.5 DEVIATION FROM STANDARDS .....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 TECHNICAL REQUIREMENTS SPECIFICATION IN EN 62311 .....	6

## 4 General Information

### 4.1 General Description of EUT

Product Name:	LoRaWAN Gateway
Model No.:	DLOS8
<b>Lora 868MHz:</b>	
Operation Frequency:	867.1MHz ~868.8MHz
Modulation type:	FSK
Antenna Type:	fibre-glass epoxy antenna
Antenna Gain:	3dBi
<b>2.4G WiFi:</b>	
Operation Frequency:	2412MHz~2472MHz(802.11b/802.11g/802.11n(HT20)) 2422MHz~2462MHz(802.11n(HT40))
Channel Separation:	13 for 802.11b/802.11g/802.11n(HT20) 9 for 802.11n(HT40)
Channel separation:	5MHz
Modulation Technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum(DSSS)
Modulation Technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Antenna Type:	Integral Antenna
Antenna gain:	0dBi
Power Supply:	AC/DC Adapter Model: TP02-120100E Input:AC100-240V, 50/60Hz Output: DC 12V, 1A

## 4.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

- **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

## 4.3 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

## 4.4 Description of Support Units

None.

## 4.5 Deviation from Standards

None.

## 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.

## 5 Technical Requirements Specification in EN 62311

Test Requirement:	EN 62311																																																												
Test Method:	EN 62311																																																												
General Description of Applied Standards	EN 62311 Generic standard to demonstrate the compliance of electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (0 Hz–300 GHz) is to demonstrate the compliance of apparatus with the basic restrictions or reference levels on exposure of the general public related to electric, magnetic, electromagnetic fields as well as induced and contact current.																																																												
Limit:	<p>According to EN 62311, the criteria listed in the below table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified table 2 of Council Recommendation 1999/519/EC.</p> <p style="text-align: center;">Reference levels for electric, magnetic and electromagnetic fields (0 Hz to 300 GHz, unperturbed rms values)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Frequency range</th> <th style="text-align: center;">E-field strength (V/m)</th> <th style="text-align: center;">H-field strength (A/m)</th> <th style="text-align: center;">B-field (μT)</th> <th style="text-align: center;">Equivalent plane wave power density <math>S_{eq}</math> (W/m<sup>2</sup>)</th> </tr> </thead> <tbody> <tr> <td>0-1 Hz</td> <td style="text-align: center;">—</td> <td style="text-align: center;"><math>3,2 \times 10^4</math></td> <td style="text-align: center;"><math>4 \times 10^4</math></td> <td style="text-align: center;">—</td> </tr> <tr> <td>1-8 Hz</td> <td style="text-align: center;">10 000</td> <td style="text-align: center;"><math>3,2 \times 10^4/f^2</math></td> <td style="text-align: center;"><math>4 \times 10^4/f^2</math></td> <td style="text-align: center;">—</td> </tr> <tr> <td>8-25 Hz</td> <td style="text-align: center;">10 000</td> <td style="text-align: center;"><math>4\ 000/f</math></td> <td style="text-align: center;"><math>5\ 000/f</math></td> <td style="text-align: center;">—</td> </tr> <tr> <td>0,025-0,8 kHz</td> <td style="text-align: center;"><math>250/f</math></td> <td style="text-align: center;"><math>4/f</math></td> <td style="text-align: center;"><math>5/f</math></td> <td style="text-align: center;">—</td> </tr> <tr> <td>0,8-3 kHz</td> <td style="text-align: center;"><math>250/f</math></td> <td style="text-align: center;">5</td> <td style="text-align: center;">6,25</td> <td style="text-align: center;">—</td> </tr> <tr> <td>3-150 kHz</td> <td style="text-align: center;">87</td> <td style="text-align: center;">5</td> <td style="text-align: center;">6,25</td> <td style="text-align: center;">—</td> </tr> <tr> <td>0,15-1 MHz</td> <td style="text-align: center;">87</td> <td style="text-align: center;"><math>0,73/f</math></td> <td style="text-align: center;"><math>0,92/f</math></td> <td style="text-align: center;">—</td> </tr> <tr> <td>1-10 MHz</td> <td style="text-align: center;"><math>87/f^{1/2}</math></td> <td style="text-align: center;"><math>0,73/f</math></td> <td style="text-align: center;"><math>0,92/f</math></td> <td style="text-align: center;">—</td> </tr> <tr> <td>10-400 MHz</td> <td style="text-align: center;">28</td> <td style="text-align: center;">0,073</td> <td style="text-align: center;">0,092</td> <td style="text-align: center;">2</td> </tr> <tr> <td>400-2 000 MHz</td> <td style="text-align: center;"><math>1,375\ f^{1/2}</math></td> <td style="text-align: center;"><math>0,0037\ f^{1/2}</math></td> <td style="text-align: center;"><math>0,0046\ f^{1/2}</math></td> <td style="text-align: center;"><math>f/200</math></td> </tr> <tr> <td>2-300 GHz</td> <td style="text-align: center;">61</td> <td style="text-align: center;">0,16</td> <td style="text-align: center;">0,20</td> <td style="text-align: center;">10</td> </tr> </tbody> </table> <p>Notes: 1. <math>f</math> as indicated in the frequency range column.</p>	Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )	0-1 Hz	—	$3,2 \times 10^4$	$4 \times 10^4$	—	1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—	8-25 Hz	10 000	$4\ 000/f$	$5\ 000/f$	—	0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—	0,8-3 kHz	$250/f$	5	6,25	—	3-150 kHz	87	5	6,25	—	0,15-1 MHz	87	$0,73/f$	$0,92/f$	—	1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—	10-400 MHz	28	0,073	0,092	2	400-2 000 MHz	$1,375\ f^{1/2}$	$0,0037\ f^{1/2}$	$0,0046\ f^{1/2}$	$f/200$	2-300 GHz	61	0,16	0,20	10
Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )																																																									
0-1 Hz	—	$3,2 \times 10^4$	$4 \times 10^4$	—																																																									
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—																																																									
8-25 Hz	10 000	$4\ 000/f$	$5\ 000/f$	—																																																									
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—																																																									
0,8-3 kHz	$250/f$	5	6,25	—																																																									
3-150 kHz	87	5	6,25	—																																																									
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—																																																									
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—																																																									
10-400 MHz	28	0,073	0,092	2																																																									
400-2 000 MHz	$1,375\ f^{1/2}$	$0,0037\ f^{1/2}$	$0,0046\ f^{1/2}$	$f/200$																																																									
2-300 GHz	61	0,16	0,20	10																																																									
Test method:	<p>According to the Far field calculation formula:</p> <p style="text-align: center;"><b>Far Field Calculation Formula</b></p> $E = \frac{\sqrt{30PG(\theta, \phi)}}{r}$ <p style="text-align: center;"><math>G</math> = antenna gain relative to an isotropic antenna  <math>\theta, \phi</math> = elevation and azimuth angles to point of investigation  <math>r</math> = distance from observation point to the antenna</p> <p>The antenna of the product, under normal use condition is at least 20cm away from the body of the user. Warning statement of the user for keeping 20cm separation distance and the prohibition of operating to a person has been printed on the user manual. So, this product under normal use is located on electromagnetic far field between the human body.</p>																																																												
Result:	Pass																																																												

**Measurement Data:**

Distance to human body: 20cm

Frequency (MHz)	ERP (dBm)	Output Power (mW)	E Field Strength (V/m)	Limit (V/m)	Result
867.9	12.46	17.620	3.635	61.0	Pass
2412~2472	16.13	41.02	5.55	61.00	Pass

-----End-----